



OFFICE DOCK

Part No. T1190-OD



VEHICLE DOCK

Part No. T1190-VED

Dock Ports

USB 3.0 (2)
Serial Port (2)
VGA (1)
Audio - Speaker & Mic
Ethernet (1)
Display Port (1)
HDMI (1)

xTablet T1190 Docks

Stay powered up and productive throughout the day with MobileDemand's office and vehicle docks for the rugged T1190. Utilize the T1190 desktop / office dock to connect external peripherals for increased productivity, designed for quick and easy tablet installation and removal. The vehicle dock is secure, lockable and built tough to withstand the rigors of the warehouse floor. We make mounting the T1190 to forklifts simple by using MobileDemand's roll cage upright post mount kit. Once mounted, you have the option of plugging into the onboard battery for continuous power.




ITEMS

SPECIFICATIONS

USB PORT

Corresponding standard	USB 3.0
Data transfer rate	600MByte/s maximum
Number of Ports	2

Arrangement of Pins




PIN	DESCRIPTION
1	Ground
2	Data +
3	Data -
4	Power (5VDC)
5	Receive -
6	Receive +
7	Ground
8	Transmit -
9	Transmit +

Shape of port connector	Type A
USB bus power (Maximum output)	5V / 0.5A USB Port Note : 2 USB port max output 1A

COM PORT

Interface Specification	RS232
Number of Ports	2
Arrangement of Ports	9
Shape of port connector	COM

Pin Assignments



PIN	DESCRIPTION
1	DCD
2	RXD
3	TXD
4	DTR
5	GND
6	DSR
7	RTS
8	CTS
9	*RI

* Power over Pin 9 via a jumper option available on port 2 only.

Baud Rate: Minimum to maximum	75 to 6M Baud Rate
Data bit	Support for 5, 6, 7 or 8 data bits
Parity	Odd, Even, Mark, Space, or None parity mode
Stop bit	1, 1.5 or 2 stop bits

Operating temperature :	-10°C ~ 50°C
Storage temperature :	-20 °C ~ 60 °C
Operating Humidity:	0% to 95% RH
Storage Humidity:	0% to 95% RH